


SPECIFICATION




LOA		12.40 m	40' 8"
Hull length		11.99 m	39' 4"
LWL		11.40 m	37' 5"
Beam		4.17 m	13' 8"
Draft			
shallow keel		1.74 m	5' 9"
L-keel, medium		2.10 m	6' 11"
Displacement			
shallow keel	approx.	10.10 t	22.267 lbs
L-keel, medium	approx.	9.80 t	21.605 lbs
Engine Diesel			
standard	approx.	39.00 PS	39.00 hp
option	approx.	57.00 PS	57.00 hp
Fuel tank	approx.	160 l	42 gal
Fresh water	approx.	475 l	125 gal
CE Certificate		A - 10	
Design		judel / vrolijk & co	
Interior		HanseYachts Design	
Mast length above WL	approx.	19.60 m	64' 4"
Total sail area	approx.	87.00 qm	936 sq ft
Main sail	approx.	52.50 qm	565 sq ft
furling	approx.	45.00 qm	484 sq ft
Self-tacking jib	approx.	34.50 qm	371 sq ft
CrossOver	approx.	76.90 qm	828 sq ft
Gennaker	approx.	120.00 qm	1.292 sq ft

418


Modell year 2018 valid 2017.07.13 Warning. Above specifications are non-contractual.




Standard



Option



Option



Option

HULL

- 6 hull windows (3 each side)
- GRP hull, isophthalic gelcoat, colour: Signal White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core.
- Waterline and cove line, isophthalic gelcoat, colour: Dark Grey (RAL 7043)

KEEL

- L-keel, cast iron, draft: 2.10 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- A1: Master cabin with double V-berth, hanging locker and shelves
- B1: Saloon with large L-galley, dining area on stb and sofa on port
 - separate head with shower stall on port (only with XL3001)
- C1: Aft cabin with double berth and storage on port, utility room on stb (only with XL2001)
- 2-burner gas stove, 12 V fridge approx. 130 l, waste bin, double stainless steel sink with mixing tab
- Interior furniture in high quality marine plywood, satin varnish
- Hanse companionway closing system
- Saloon table, folding with stowage
- Worktop in galley - Black Quartz

WOOD (FURNITURE, FLOORBOARD)

- Furniture - Mahogany Style, Satin Varnish
- Cupboard fronts in wood colour
- Floorboard - Acacia

UPHOLSTERY, CARPETS & CURTAINS

- Mattresses for all berths
- Upholstery - Monte Carlo, colour: Cream

DECK & OUTSIDE EQUIPMENT

- GRP deck with antislip surface, isophthalic gelcoat, colour: Signal White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core. 1 cockpit locker on stb, stern locker on port and stb, stowage for running rigging at helm position, anchor locker at bow.
- Teak on cockpit benches
- Twin wheel steering system with emergency tiller

- 2 stainless steel steering wheels with leather cover
- Cockpit table, stainless steel with folding teak tops
- Pulpit and pushpit, stainless steel
- Railing, incl. stanchions and stainless steel wire
- Covered halyards and control lines lead to cockpit helm position, organizers and jammers, 4 mooring cleats, handrail on coach roof, bow anchor fitting with step

- 2 LEWMAR 45 ST EVO manual halyard winches
- Swimming ladder
- Self tacking jib system
- Mainsheet system
- 2 deck hatches - openable, anchor locker hatch, stowage on coach roof with acrylic glass hatch
- 6 deck coach roof windows with openable portlight in bathroom, glass next to companionway, glass in saloon and master cabin portlight in cockpit side for aft-cabin port

RIG & SAILS

- Rig, anodized aluminium, deck stepped, with kicker, standing and running rigging and 2 reefs
- ELVSTRÖM Dacron sails - full battened, main and jib

NAVIGATION & INSTRUMENTS

- Illuminated compass
- Navigation lights - LED

PROPULSION

- Fuel tank, approx. 160 l
- Engine (Diesel, approx. 39 hp) - saildrive, 2-blade fix propeller

EQUIPMENT

- 12 V and 230 V electric system with main panels and 230 V shore power and sockets.
- AGM battery set, capacity: 1x 90 Ah + 1x 160 Ah AGM
- Country Version: EU / AUS
- Battery charger 35 A
- Manual toilet with sea water flush (B layout)
- Manual toilet with sea water flush (A layout)
- Shower unit in cockpit, warm-/coldwater
- LPG gas system, 1 bottle in stowage

- Blackwater system (appr. 65 l) with deck extraction and seacock for head, electric and manual bilge pump
- Freshwater system with electric pump and 20 l hotwater, heated by main engine
- Fresh water tank, appr. 320 l
- Add. freshwater tank, appr. 200 l

ACCESSORIES

- Mast steps

SHIPPING & TRANSPORT

- CE - Certificate cat. A - 10
- Owners manual
- EC - Type Examination Certificate