

| specification |
|---------------|
| DS 41 |
| |

| Beam | 4.20 m | 13' 9'' |
|-------------------------|----------------------|------------|
| Draft | 1.85 m | 6' 1'' |
| | | |
| Displacement approx. | 11.90 t | 24,250 lbs |
| Ballast approx. | 3.13 t | 6,900 lbs |
| Engine approx. | Diesel 41.9 kW | 57 hp |
| Fresh water | 475 | 125 gal |
| Fuel tank | 210 | 55 gal |
| CE Certifcate | A - 12 | |
| Mast lenght above WL | 19.90 m | 65' 3" |
| Main approx. | 45.00 m ² | 484 sq ft |
| Jib approx. | 38.00 m ² | 409 sq ft |
| Total sail area approx. | 83.00m ² | 893 sq ft |
| Rlg | l 16.8 m | 55' 1'' |
| | J 4.7 m | 15' 5" |
| | P 16.2 m | 53' 2'' |
| | E 5.5 m | 18' 1'' |
| Design | Dixon Yacht Design | |
| Interior | Hanse Design Team | |

12.52 m

11.42 m

41'1''


37' 6"

LOA

LWL



Model year 2020. Valid from 2019.07.01. All measurements/figures are approximate. Errors and omissions excepted. Specification and material can be changed without notice.



standard specification DS41

HULL

- · 5 hull windows (3 on stb, 2 on port)
- · GRP hull, isophthalic gelocat: Off White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core.
- · Waterline and cove line, isophtalic gelcoat colour: Moody Grey (RAL 7034)

KEEL

- · L-keel, cast iron, draft: 1.85 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- · A1: Master cabin with island double berth, storage space and head with separate shower stall
- · B1: Guest cabin with double berth, storage and utility room
- · C1: Saloon with full functional L-galley and dining area on stb - chart table on port
- · 3-burner gas stove with oven, waste bin, 12 V fridge approx. 140 I, sink with mixing tab
- · Interior furniture in high quality marine plywood, satin varnished
- Sliding door in deckhouse
- · Worktop in galley Corian, colour: Grained Black

WOOD (FURNITURE, FLOORBOARD)

- · Furniture Traditional Mahogany satin varnish
- · Floorboard New Zealand Acacia

UPHOLSTERY. CARPETS & CURTAINS

- Comfort mattrasses for all berths
- · Upholstery kent, colour: Cream

DECK & OUTSIDE EQUIPMENT

- · GRP deck with antislip surface, gelcoat colour; Off White (RAL 9003), 1st layer vinyl ester resin with blasa sandwich core.
- Teak on cockpit bottom
- Teak on helmsman seats
- Teak on cockpit benches
- Teak on bathing platform
- · Twin wheel steering system with emergency tiller
- · 2 stainless steel steering wheels with leather cover
- · Cockpit table, stainless steel with folding teak tops
- · Pulpit and pushpit, stainless steel
- · Railing, stainless steel tube and wire, incl. integrated boarding ladder on both sides and swimming ladder
- Halyards and control lines in cockpit at helm position, stern locker, 2 cockpit lockers, stowage for running rigging at helm position, 6 retractable mooring cleats, handrail on coach roof, anchor arm and anchor locker

- · 2 LEWMAR 45 EST EVO electrical halyard winches
- · Bathing platform, manual fold-out with swimming ladder
- · 2 helmsman seats, foldable (only with XC1333 or XC1334)
- · Delta-anchor 25 kg, galvanized with 60 m galvanized chain, dia. 10 mm
- · Self tacking jib system
- · German mainsheet system
- Panoramic deckssaloon windows, central glass surface for deckssaloon with 2 openable hatches, skylight for guest cabin in deckssaloon, 1 fwd. coachroof front window. 2 coachroof hatches (for heads - milked), 3 mitre-cut portlights on coachroof sides, glass surface on forward coachroof with a big openable hatch (sz. 70)

RIG & SAILS

- · Rig, anodized aluminium, deck stepped, with kicker, standing and running rigging and 2 reefs · Bimini with sliding mechanism (colour selection)
- · ELVSTRÖM Dacron sails full battened, main and
- jib

NAVIGATION & INSTRUMENTS

- · Illuminated compass at each helm
- Navigation lights LED

PROPULSION

- · Fuel tank, approx, 410 |
- · Engine (Diesel, approx. 57 hp) saildrive, 2-blade fixed propeller

FOUIPMENT

- · 12 V and 230 V electric system, 230 V shore power and sockets in cabins and heads
- · Battery set, capacity: 1x 90 Ah + 1x 160 Ah AGM
- · Country Version: EU / AUS
- Battery charger 50 A
- Shore power 230 V or 110 V
- · Manual toilet with sea water flush (master cabin)
- · Shower unit in cockpit, warm-/coldwater
- · LPG gas system, stowage for 2 bottles
- · Blackwater system (appr. 50 | per head) with deck extraction and seacock for head
- Freshwater system with electric pump and 40 I hotwater, heated by main engine
- · Fresh water tank, appr. 220 I
- · Add. fresh water tank, appr. 180 |

standard specification DS41

ACCESSORIES

- \cdot Wind indicator
- \cdot Flagpole
- · 6 fenders
- \cdot 4 mooring lines

SHIPPING & TRANSPORT

- · CE Certificate cat. A 12
- \cdot Owners manual
- \cdot EC Type Examination Certificate