
# **SPECIFICATION**



	HANSE 325
LOA	9.63 m   31´6″
Hull length	9.55 m   31´3″
LWL	8.72 m   28′6″
Beam	3.30 m   10'8″
Draft	1.84 m   6´ (standard)
	1.53 m   5´ (option)
Displacement	approx. 5.2 t   approx. 11,464 lb
Ballast	approx. 1,480 kg   approx. 3,263 lb (standard)
	approx. 1,700 kg   approx. 3,747 lb (option)
Engine	13.3 kW / 18 HP
Fresh water	approx. 240 l
Fuel tank	approx. 90 l
CE Certificate	A (ocean)
Mast length above WL	approx. 14.77 m   approx. 48'5"
Total sail area	approx. 51.35 m²   approx. 553 sq ft
Main sail	approx. 28.47 m <sup>2</sup>   approx. 306 sq ft
Self-tacking jib	approx. 22.87 m <sup>2</sup>   approx. 246 sq ft
Rig	l 12.45 m   40´8″

Design

Interior

Modell year 2014/2015 - valid from September, 2014

J 3.87 m | 12'7" P 11.70 m | 38'4" E 4.10 m | 13'5"

judel / vrolijk & co

HanseYachts Design









# STANDARD EQUIPMENT

# HULL

- White hull
- Dark grey double waterlines Options for different hull colour according to
- Hanse colour selection Vinylester 1<sup>st</sup> layer
- Bulk laminate Polyester (orthophtalic or DCPD)
- Solid laminate Main bulkhead laminated to hull and deck
- GRP strongbacks

# DECK

- White deck Isophtalic Gelcoat
- Vinylester 1<sup>st</sup> layer Bulk laminate Polyester (Orthophatalic or DCPD)
- Balsa sandwich Non-slip deck surface
- STEERING SYSTEM

# Steering wheel with instrument console

Semi-balanced, profiled rudder with allov shaft and self aligning needle bearings

### KEEL

- Cast iron T-speed keel with low centre of gravity
- Deep draft: 1.84 m / 6"
- Option: Shallow draft 1.53 m / 5"
- Stainless steel keel bolt

## DECK EQUIPMENT

- Self-draining anchor locker with lockable hatch Self-draining cockpit
- 2 opening hatches (fwd. cabin, saloon) 6 opening port lights
- 4 mooring cleats
- 2 combined self tailing halyard & jib sheet winches 40 AST
- Halyards lead aft to cockpit 1 winch handle
- Bow fitting with anchor roller and pad eye
- 8 halyard stoppers
- Pulpit
- Pushpit with ensign staff socket Sliding hatch garage
- Sliding hatch
- Wash board
- Double stainless steel wire guard rail
- Teak on cockpit benches
- Swimming ladder

# TECHNICAL SYSTEM

#### PLUMBING SYSTEM / FRESH WATER Tank

Fresh water capacity approx. 240 I Water infill at anchor locker

All measurements are approximate. Specification and material can be changed without notice

HanseYachts AG I Ladebower Chaussee 11 I D-17489 Greifswald

- Pumps
- Electrical pressurised water system Faucets
- Faucets in galley and head

www.hanseyachts.com

# DRAINING PUMPS

- Bilge pumps
- 1 manual bilge pump 1 electric bilge pump

#### Toilet / Head Holding tank

- Sea and deck discharge
- 1 manual marine toilet

## ENGINE

- Volvo D1-20 13,3 kW / 18 HP, diesel engine
- Fresh water cooling Saildrive
- 2-blade fixed propeller
- Fuel tank, approx. 90 I Fuel infill on deck
- Sea water strainer Fuel filter / Water separator
- Revolution counter
- Engine hour meter
- Engine room sound insulated

### ELECTRICS

- 12 V electrical circuits
- Voltmeter Water / Fuel gauges
- Batteries Main battery switch
- 1 Engine battery: 12 V / 90 Ah AGM 1 Service battery: 12 V / 90 Ah AGM
- Electric control panel 12 V
- 12 V outlet Voltmeter
- Fuel gauge
  Interior lighting

#### in galley in head

- Navigation lights
- Steaming light Bow light
- Stern light
- Anchor light
- Navigation instruments Illuminated compass

## GALLEY

- Quartz black surface
- Stainless steel sink
- 2-burner LPG stove with oven, gimbled Locker and drawers
- Insulated coolbox
- LPG gas system

## INTERIOR ACCOMMODATION

- Interior in "Ohio cherry" style
- Floorboards Classic style White bulkheads
- Sandwich doors
- Upholstery

#### According to Hanse colour selection Forward cabin

- Separated from saloon by a door
- Large double berth
- Hanging locker
- Aft cabin
- Separated from saloon by a door Large double berth
- Combined hanging locker and shelve

Locker for all navigation equipment

Holding tank with sea and deck discharge

2 spreader anodised aluminium mast and boom Furling system for jib

Stainless steel standing rigging, discontinous

Main sail with 2 reefs, one Full batten and 3 short Self-tacking jib with traveller

Valancia Upholstery selection B&G Triton multifuction display with Log Depth

Teak on cockpit bottom & Helmsman seats Footrests for Helmsman

Shower unit in cockpit Hot & Cold water

B&G Triton multifuction display with Edg Dopur B&G Triton multifuction display with Wind transducer B&G zeus Touch 8 GPS Plotter

Spring Cleats Anchor "Delta" 10kg with 30 chain Battery upgrade set to 1x 90Ah and 1x 160Ah AGM

Adjustable backstay Main and jib halyard lead aft to cockpit

Hull colour in light grey (Ral 7047) Waterline in white

Option: Shower & drain pump

Hanse single line reefing system

Saloon

Head / Shower

Sink

Locker

Mirror

Marine toilet

Opening port light

(cockpit handling)

Main and jib sheets

MAXIMUM EDITION

Charger 30A Shorepower

\_

Lazy bag Sprayhood

Shower unit in head Waterheater 20I Wind indicator

4 Fenders and Mooring lines Second winch handle Maintenance kit Vent on coachroof

Readinglights in saloon & cabins LED overhead lights Cockpit cushions Blind set for hatches Blinds for side windows

Cockpit portlight aft cabin Opening hatch for head and aft cabin

2 lewmar 40ST manual secondary winches

anse //

AKING RULES . SETTING TRENDS

**RIGG AND SAILS** 

9/10-rig

Door to storage room

- Companionway Settee on both sides
- Saloon table Lockers and shelves Navigation area

Navigation seat Chart table with storage

Electric switch panel